







DA20 (Y201)

PREMIUM STEER/ ALL-POSITION TIRE

STEER

- 5-rib tread pattern including wide shoulders promotes durability and even wear in all-positions
- Enhanced siping and wide grooves allows for premium traction in both wet and dry conditions
- ▶ Full size complement from 19.5" to 24.5" rim diameters



TIRE SIZE	PLY RATING	LOAD RANGE	RIM (INCH)	TREAD DEPTH (32NDS)	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	SINGLE MAX LOAD/PRESSURE (LB/PSI)	SPEED SYMBOL	WEIGHT (LB)
11R22.5	14	G	8.25	19	41.4	11.0	6175/105	М	118
11R22.5	16	Н	8.25	19	41.4	11.0	6610/120	М	118
315/80R22.5	18	J	9.00	20	42.5	12.2	8820/120	М	141
11R24.5	14	G	8.25	19	43.3	11.0	6610/105	L	128
11R24.5	16	Н	8.25	19	43.3	11.0	7160/120	L	128
12.00R24	20	L	8.50	20	48.0	12.2	9920/130	K	149
12R22.5	18	J	9.00	21	42.7	11.8	7830/135	L	134
225/70R19.5	12	F	6.75	16	31.9	8.9	3640/95	М	66
225/70R19.5	14	G	6.75	16	31.9	8.9	3969/110	М	66
315/70R22.5	18	J	9.00	18	40.0	12.3	7610/120	М	137
245/70R19.5	16	Н	7.50	16	33.0	9.8	4940/120	L	81
265/70R19.5	16	Н	7.50	16	34.3	10.0	6005/123	K	89
285/75R24.5	14	G	8.25	19	41.5	11.1	6175/110	М	120
295/60R22.5	18	J	9.00	20	36.5	11.5	7390/130	L	106
295/75R22.5	14	G	9.00	19	40.6	11.7	6175/110	М	117
295/80R22.5	18	J	9.00	19	41.2	11.7	7830/130	М	122



DS28 (Y208)

PREMIUM DECOUPLING GROOVE STEER TIRE

STEER

- 5-rib tread design with special tread compounds enhances even wear, traction in long haul steer axle positions
- Multiple sipes and decoupling grooves enhance tire wear and traction
- Durable casing design to promote retreading



TIRE SIZE	PLY RATING	LOAD RANGE	RIM (INCH)	TREAD DEPTH (32NDS)	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	SINGLE MAX LOAD/PRESSURE (LB/PSI)	SPEED SYMBOL	WEIGHT (LB)
11R22.5	14	G	8.25	19	41.4	11.0	6175/105	М	118
11R22.5	16	Н	8.25	19	41.4	11.0	6610/120	М	118
11R24.5	14	G	8.25	19	43.3	11.0	6610/105	L	128
11R24.5	16	Н	8.25	19	43.3	11.0	7160/120	L	128
285/75R24.5	14	G	8.25	19	41.5	11.1	6175/110	М	120
295/75R22.5	14	G	9.00	19	40.6	11.7	6175/110	М	117

PREMIUM STEER/ ALL-POSITION TIRE

STEER

- 5-rib tread pattern including wide shoulders promotes durability and even wear in all-positions



TIRE SIZE	PLY RATING	LOAD RANGE	RIM (INCH)	TREAD DEPTH (32NDS)	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	SINGLE MAX LOAD/PRESSURE (LB/PSI)	SPEED SYMBOL	WEIGHT (LB)
12R22.5	18	J	9.00	20	42.7	11.8	7830/135	L	133



PREMIUM ON/OFF HIGHWAY MIXED SERVICE ALL-POSITION TIRE

STEER

- Strong all-position tread pattern designed for multiple on/off highway uses
- Heavy-duty casing construction for excellent performance in tough application



TIRE SIZE	PLY RATING	LOAD RANGE	RIM (INCH)	TREAD DEPTH (32NDS)	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	SINGLE MAX LOAD/PRESSURE (LB/PSI)	SPEED SYMBOL	WEIGHT (LB)
7.00R16LT	14	G	5.50F	17	30.5	7.9	2910/112	М	55



PREMIUM OPEN SHOULDER **DRIVE-POSITION TIRE**

DRIVE

- Innovative open shoulder tread design provides enhanced traction in multiple applications



TIRE SIZE	PLY RATING	LOAD RANGE	RIM (INCH)	TREAD DEPTH (32NDS)	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	SINGLE MAX LOAD/PRESSURE (LB/PSI)	SPEED SYMBOL	WEIGHT (LB)
11R22.5	14	G	8.25	25	41.7	11.0	6175/105	М	123
11R22.5	16	Н	8.25	25	41.7	11.0	6610/120	М	123
315/80R22.5	18	J	9.00	28	43.2	12.5	8820/120	L	161
11R24.5	14	G	8.25	25	43.7	11.0	6610/105	L	135
11R24.5	16	Н	8.25	25	43.7	11.0	7160/120	L	135
12R22.5	18	J	9.00	28	43.0	11.9	7830/135	L	156
285/75R24.5	14	G	8.25	25	41.9	11.1	6175/110	L	126
295/75R22.5	14	G	9.00	25	40.9	11.7	6175/110	L	122
295/80R22.5	18	J	9.00	28	41.8	11.7	7830/130	М	130



ULTRA PREMIUM CLOSED SHOULDER DRIVE-POSITION TIRE

DRIVE

- Closed shoulder design promotes long, even treadwear while maintaining excellent traction
- Extra deep 30/32" original tread depth suitable for all applications
- Durable casing allows for multiple retreads



TIRE SIZE	PLY RATING	LOAD RANGE	RIM (INCH)	TREAD DEPTH (32NDS)	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	SINGLE MAX LOAD/PRESSURE (LB/PSI)	SPEED SYMBOL	WEIGHT (LB)
11R22.5	14	G	8.25	30	41.9	11.0	6175/105	L	129
11R22.5	16	Н	8.25	30	41.9	11.0	6610/120	L	129
11R24.5	14	G	8.25	30	43.9	11.0	6610/105	L	138
11R24.5	16	Н	8.25	30	43.9	11.0	7160/120	L	138
315/70R22.5	18	J	9.00	28	41.0	12.3	7610/120	М	NA
285/75R24.5	14	G	8.25	30	41.6	11.1	6175/110	L	127
295/60R22.5	18	J	9.00	28	36.5	11.5	7390/130	L	NA
295/75R22.5	14	G	9.00	30	40.2	11.7	6175/110	L	121



PREMIUM LOW PROFILE DRIVE-POSITION MULTI-USE TIRE

DRIVE

- Innovative tread design and compounds promotes excellent traction and resist irregular wear
- Durable casing construction perfect for tough regional
- Deep original tread depth provides maximum tread life



TIRE SIZE	PLY RATING	LOAD RANGE	RIM (INCH)	TREAD DEPTH (32NDS)	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	SINGLE MAX LOAD/PRESSURE (LB/PSI)	SPEED SYMBOL	WEIGHT (LB)
11R22.5	16	Н	8.25	25	41.9	11.0	6610/120	L	123
315/80R22.5	18	J	9.00	25	42.5	12.2	8270/120	М	161
12R22.5	18	J	9.00	25	43.2	11.9	7830/135	L	160
315/70R22.5	18	J	9.00	24	40.4	12.3	7610/120	М	144
13R22.5	18	J	9.75	26	44.7	12.6	8270/120	K	160
295/60R22.5	18	J	8.50	20	48.0	12.2	7390/130	L	150



PREMIUM LOW PROFILE MULTI-USE DRIVE TIRE

DRIVE

- Innovative tread design and compounds promote excellent traction and resist irregular wear
- ▶ Deep original tread depth provides maximum tread life
- Durable casing construction perfect for tough regiona and urban use



TIRE SIZE	PLY RATING	LOAD RANGE	RIM (INCH)	TREAD DEPTH (32NDS)	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	SINGLE MAX LOAD/PRESSURE (LB/PSI)	SPEED SYMBOL	WEIGHT (LB)
225/70R19.5	14	G	6.75	19	32.6	8.8	3970/110	L	68
245/70R19.5	14	G	7.50	19	33.5	9.6	4540/110	L	84
265/70R19.5	16	Н	7.50	22	34.6	10.0	6005/123	L	86
265/70R19.5	18	J	7.50	22	34.6	10.0	6175/125	L	86



PREMIUM SHALLOW DEPTH TRAILER-POSITION TIRE

TRAILER

- Enhanced siping provides traction and fights



TIRE SIZE	PLY RATING	LOAD RANGE	RIM (INCH)	TREAD DEPTH (32NDS)	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	SINGLE MAX LOAD/PRESSURE (LB/PSI)	SPEED SYMBOL	WEIGHT (LB)
11R22.5	14	G	8.25	12	41.0	11.0	6175/105	М	106
11R24.5	14	G	8.25	12	42.9	11.0	6610/105	L	114
295/75R22.5	14	G	9.00	12	40.2	11.7	6175/110	М	102
285/75R24.5	14	G	8.25	12	41.1	11.1	6175/110	L	110



PREMIUM LOW PROFILE MULTI-**USE TRAILER-POSITION TIRE**

TRAILER

- Special tread compounds allow for long life in trailer and
- 5-rib design promotes traction and long life



TIRE SIZE	PLY RATING	LOAD RANGE	RIM (INCH)	TREAD DEPTH (32NDS)	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	SINGLE MAX LOAD/PRESSURE (LB/PSI)	SPEED SYMBOL	WEIGHT (LB)
215/75R17.5	16	Н	6.00	16	30.2	8.3	4805/125	L	61
235/85R16	14	G	6.50	12	30.7	9.5	3750/112	L	64
255/70R22.5	16	Н	7.50	13	36.6	10.0	5510/120	Ν	88
235/75R17.5	16	Н	6.75	16	31.4	9.2	6010/125	L	70
7.00R16LT	14	G	5.50F	15	30.5	7.9	2910/112	М	53
7.50R16	14	G	6.00G	16	31.7	8.3	3305/112	М	56
275/70R22.5	16	Н	8.25	16	37.7	10.9	6940/130	М	108



MIXED SERVICE SERVICE ALL-POSITION TIRE

- Strong all-position tread pattern designed for multiple on/off highway uses



TIRE SIZE	PLY RATING	LOAD RANGE	RIM (INCH)	TREAD DEPTH (32NDS)	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	SINGLE MAX LOAD/PRESSURE (LB/PSI)	SPEED SYMBOL	WEIGHT (LB)
11R22.5	16	Н	8.25	22	41.4	11.0	6610/120	L	121
315/80R22.5	18	J	9.00	22	42.5	12.2	8820/120	М	141
12.00R24	20	L	8.50	20	48.0	12.2	9920/130	K	150
12R22.5	18	J	9.00	22	42.7	11.8	7830/135	L	133
13R22.5	18	J	9.75	22	42.4	12.6	8270/120	K	155



SERVICE DRIVE-POSITION TIRE

MIXED SERVICE

- Extra deep 33/32" tread depth for on/off road
- Chip and cut resistant compounds offer long mileage



TIRE SIZE	PLY RATING	LOAD RANGE	RIM (INCH)	TREAD DEPTH (32NDS)	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	SINGLE MAX LOAD/PRESSURE (LB/PSI)	SPEED SYMBOL	WEIGHT (LB)
11R22.5	16	Н	8.25	33	43.0	11.1	6610/120	G	129
11R24.5	16	Н	8.25	33	44.0	11.1	7160/120	G	138



PREMIUM ON/OFF HIGHWAY ALL-POSITION TIRE

MIXED SERVICE

- Wide all-position tread pattern designed for multiple on/off highway uses
- Heavy-duty casing construction for excellent performance in tough applications
- Available in tubeless and tube-type sizes



TIRE SIZE	PLY RATING	LOAD RANGE	RIM (INCH)	TREAD DEPTH (32NDS)	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	SINGLE MAX LOAD/PRESSURE (LB/PSI)	SPEED SYMBOL	WEIGHT (LB)
10.00R20	16	Н	7.50	21	41.5	10.9	6610/120	K	140
11.00R20	18	J	8.00	21	42.7	11.5	7830/135	K	155
11R22.5	16	Н	8.25	19	41.4	11.0	6610/120	М	118
315/80R22.5	18	J	9.00	20	42.5	12.2	8820/120	М	141
315/80R22.5	22	М	9.00	20	42.5	12.2	10000/130	65MPH	141
12.00R20	18	J	8.50	22	44.3	12.4	8270/120	K	164
11R24.5	16	Н	8.25	19	43.3	11.0	7160/120	L	128
12.00R24	20	L	8.50	20	48.0	12.2	9920/130	K	149
12R22.5	18	J	9.00	21	42.7	11.8	7830/135	L	134
9.00R20	16	Н	7.00	19	40.1	10.2	6170/130	K	110



ULTRA PREMIUM WIDE BASE MIXED SERVICE ALL-POSITION TIRE

MIXED SERVICE

- Aggressive multi-purpose tread design ideal for on/off highway applications
- Large tread elements offer improved handling and



TIRE SIZE	PLY RATING	LOAD RANGE	RIM (INCH)	TREAD DEPTH (32NDS)	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	SINGLE MAX LOAD/PRESSURE (LB/PSI)	SPEED SYMBOL	WEIGHT (LB)
425/65R22.5	20	L	13.00	22	44.6	16.3	11400/120	K	199
385/65R22.5	20	L	11.75	22	42.2	14.8	9920/130	K/L	164



PREMIUM WIDE BASE ALL-POSITION TIRE

MIXED SERVICE

- Tread pattern and heavy ply rating designed for multiple uses
- Extra wide 5-rib design excellent for free rolling applications
- Durable casing provides long original tread life and promotes multiple retreads



TIRE SIZE	PLY RATING	LOAD RANGE	RIM (INCH)	TREAD DEPTH (32NDS)	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	SINGLE MAX LOAD/PRESSURE (LB/PSI)	SPEED SYMBOL	WEIGHT (LB)
435/50R19.5	18	J	14.00	17.5	36.9	17.2	8820/123	L	NA
385/55R22.5	18	J	12.25	20	39.2	15.0	9370/123	L	161
385/65R22.5	20	L	11.75	20	42.0	14.8	9920/130	K/L	164



PREMIUM ON/OFF HIGHWAY SEVERE SERVICE DRIVE-**POSITION TIRE**

MIXED SERVICE

FEATURES & BENEFITS

- Chip and cut resistant compounds offer long mileage
- Aggressive tread offers excellent traction for severe



10.00R20 18 7.50 24 41.5 10.9 7160/135 150

LIMITED MANUFACTURER'S WARRANTY



LIMITED WARRANTY

Duraturn Radial TBR (Truck and Bus Radial) Tire Limited Manufacturers Warranty January 1, 2014.

TO OBTAIN AN ADJUSTMENT

- a. You must present the tire to be adjusted to a current Duraturn Commercial Truck Tire Dealer. (Please consult your telephone directory for locations or visit our dealer locator on our website at www.duraturntires.com). Tires replaced on an adjustment basis become the property of Duraturn.
- You must pay for taxes, fees or any additional services you order at the time of adjustment.
- c. No claim will be recognized unless submitted on a Duraturn claim form (supplied by the Duraturn Commercial Truck Tire Dealer), completely filled out and signed by you, the owner of the tire presented for adjustment, or your authorized agent.

- prescribed tire identification numbers and are not branded "NA" (Not Adjustable).
- Your Duraturn truck tires have been used only on the vehicle on which they were originally installed according to the vehicle manufacturers or Duraturn recommendations.
- Your tires were purchased on or after January 1, 2014.

WHAT IS COVERED UNDER THIS WARRANTY AND FOR HOW LONG

PRORATED TIRE REPLACEMENT Duraturn truck tires covered by this warranty that become unserviceable due to a defect in workmanship or material during the life of the original usable tread (down to 2/32" remaining usable tread), will be reimbursed to the owner on a prorated basis. You pay only for the mounting, balancing, taxes and fees.

HOW TO CALCULATE THE PRORATED AMOUNT

The replacement price will be calculated by multiplying the current Duraturn "predetermined price for adjustment" or current advertised selling price at the adjustment location (whichever is lower) by the percentage of usable original tread that has been worn off at the time of adjustment. You pay for mounting, balancing, and amount equal to the full current Federal Excise Tax and any other applicable taxes and fees for the comparable new Duraturn replacement tire.

PRORATED REIMBURSEMENT EXAMPLE

If your disabled tire had an original 16/32" of usable tread depth and is worn to 8/32" of usable tread remaining you have used 50% and therefore must pay 50% of the predetermined price for adjustment or advertised selling price of a comparable tire, plus an amount equal to the full current Federal Excise Tax applicable to the comparable new replacement tire at the time of adjustment. If the price of the comparable tire is \$400.00, the cost to you would be \$200.00 plus Federal Excise Tax, mounting, balancing and any other applicable taxes.

WHO IS ELIGIBLE FOR WARRANTY COVERAGE

You are eligible for the benefits of this warranty if you meet all the following criteria:

- You are the owner or authorized agent of the owner of new Duraturn Truck Bus Radial (TBR) tires.
- Your tires bear Department of Transportation (DOT)

LIMITED MANUFACTURER'S WARRANTY

DEFINITION OF A COMPARABLE TIRE

A "comparable" new Duraturn tire may either be the same line of tire or, in the event that the same tire is not available, a tire of the same basic construction and quality with a different sidewall or tread configuration. If a higher priced tire is accepted as replacement, the difference in price will be at an additional charge to you.

Any replacement tire provided pursuant to this warranty will be covered by the Duraturn warranty in effect at the time of replacement.

WHAT THIS WARRANTY DOES NOT COVER

IRREGULAR WEAR OR TIRE DAMAGE DUE TO:

- Road hazards (including punctures, cuts, snags, impact breaks, etc.)
- Wreck, collision, or fire.
- Improper inflation, overloading, high speed spinup, misapplication, misuse, negligence, racing, chain damage, or improper mounting or demounting.
- Mechanical condition of the vehicle.
- Ride disturbance after the first 2/32" treadwear or due to damaged wheels or any vehicle condition.
- Any tire intentionally altered after leaving a factory producing Duraturn tires to change its appearance (example: white inlay on a black tire).
- Tires with weather cracking which were purchased more than five (5) years prior to presentation for adjustment. If you have no proof of purchase date, tires manufactured five (5) or more years prior to presentation are not covered.
- This limited warranty is applicable only in the United States, Canada & Mexico, and any tire used or equipped on a vehicle registered or operated outside the U.S., Canada & Mexico are not covered by this warranty.
- Tire branded or marked "Non-Adjustable" (N/A)

or "Blemished" (Blem), or previously adjusted.

FAILURE, DAMAGE, OR IRREGULAR WEAR DUE TO:

- Accident or vandalism, improper misalignment, wheel imbalance, faulty shocks or brakes:
- Mechanical condition of vehicle, including misalignment, wheel imbalance, faulty shocks or brakes:
- Misapplication of tire, use of improper inner tube;
- Alteration of the tire or addition of alien material or transfer from one vehicle to another; and
- ▶ Radial truck tire failed due to faulty retreading or material.
- Cost of mounting and balancing service except as noted above.
- Loss of time or use, inconvenience, or any incidental or consequential damages.
- ▶ Material added to a tire after leaving a factory producing Duraturn tires: (example: tire fillers, sealants, or balancing substances). If the added material is the cause of the tire being removed from service, the tire will not be adjusted.
- Loss of time, inconvenience, loss of use of vehicle, incidental or consequential damage.

YOUR LEGAL RIGHTS

Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusions may not apply to you.

No representative or dealer has authority to make any representation, promise, or agreement on behalf of Duraturn, except as stated herein.

Any tire, no matter how well constructed, may fail in service or otherwise become unserviceable due to conditions beyond the control of the manufacturer. Under no circumstances is this warranty a representation that a tire failure cannot occur.

This warranty gives you specific legal rights, and you may also

LIMITED MANUFACTURER'S WARRANTY



have other rights that vary from state to state.

This limited warranty is applicable only in the United States, Canada & Mexico.

END OF WARRANTY

A tire has delivered its full original tread life and the new tire coverage of this warranty ends when the treadwear indicators become visible, or five (5) years from the date of original tire manufacture or new tire purchase date. (Without proof of purchase, date of manufacture will be used to determine age.) Casings may continue to be warranted beyond the new tire coverage. Please refer to the Radial Casing Provision for warranty details on casings.

THE DURATURN RADIAL CASING PROVISION

Truck Tire Casings will be warranted against defects in workmanship or material through a period of five (5) years from the date of the casings DOT serial number or proof of purchase, if available, whichever comes first. If a Duraturn truck tire dealer examines a casing and finds such a defect, Duraturn will reimburse the owner for the casing according

SAFETY WARNINGS

Serious injury or property damage may result from:

- TIRE FAILURE DUE TO UNDERINFLATION/ OVERLOADING. Follow the owner's manual or tire placard in vehicle.
- TIRE FAILURE DUE TO EXCESSIVE HIGH SPEED.
 Follow the owner's manual or tire placard in vehicle.
- EXPLOSION OF TIRE/ RIM ASSEMBLY DUE TO IMPROPER MOUNTING. Only specially trained persons should mount tires.
- FAILURE TO MOUNT RADIAL TIRES ON APPROVED RIMS.
- ▶ FAILURE TO DEFLATE SINGLE OR DUAL ASSEMBLIES COMPLETELY BEFORE DISMOUNTING.
- ➤ TIRE SPINNING. On slippery surfaces such as snow, mud, ice, etc., do not spin tires in excess of 35 mph (55 kpm), as indicated on the speedometer. Personal injury and severe damage may result from excessive wheel spinning, including tire disintegration or axle failure.





